FS Low Ash Natural Gas Engine Oil

Features and Benefits:

- Specially formulated for the most severe natural gas applications in all makes of natural gas fired engines
- Protects against high-temperature oxidation and nitration
- Provides superior protection against deposit formation
- Blended with high-quality, selected base oils and additives to provide superior engine cleanliness and extend oil life

Meets or Exceeds:

- Caterpillar 3600 Series
- Caterpillar 3500 Series
- Waukesha 7044
- Waukesha 7042

Always check owner's manual for proper recommendation.

Product Availability:

FS Low Ash 30		FS Low Ash 40	
5 Gal. Pail	Item #200656	55-gal. Drum	Item #213868
55-gal. Drum	Item #197353	265-gal. Totes	Item #267852
Bulk	Item #159224	Bulk	Item #182190

Typical Properties:

Test / Description	Specification		
SAE Grade	30	40	15W-40
Viscosity @ 100°C (cSt)	11	15.5	15
Viscosity @ 40°C (cSt)	95.5	165.5	115.5
Viscosity Index	100	95	135
Density (lb/gal)	28.7	27.8	29.5
CCS Viscosity (cP)	NA	NA	6,100
Pour Point (°C)	-21	-12	-24
Pour Point (°F)	-6	10	-11
Flash Point (°C)	220	230	215
Flash Point (°F)	430	445	420
TBN	NA	NA	NA
Sulfated Ash	0.35%	0.35%	0.35%

